35-0107





2015 MAY 20 PM 1: 06

Tennessee Valley Authority, 1101 Market Street, Chattanooga, TN 37402-2801

RECEIVED

May 7, 2015

Mr. Barry Stephens, P.E. Director
Division of Air Pollution Control
Tennessee Department of Environment
and Conservation
Tennessee Tower William R. Snodgrass Building
312 Rosa L Parks Avenue
Nashville, Tennessee 37243

Dear Mr. Stephens:

TENNESSEE VALLEY AUTHORITY (TVA) – NEWCASTLE MICROWAVE STATION - CONSTRUCTION APPLICATION FOR EMERGENCY GENERATOR

Please find enclosed the referenced construction permit application. This application is to construct one new 43.5 hp propane-powered emergency generator at TVA's Newcastle Microwave Station.

If you have any questions or comments concerning this correspondence, please contact Jack Byars at (423) 751-2666 in Chattanooga, Tennessee.

Sincerely,

Billy R. Hall, Jr General Manager

Telecom and Control Systems

Enclosures

1.6



970315

CONSTRUCTION PERMIT APPLICATION FOR PROPANE ENGINE FOR EMERGENCY GENERATOR AT NEWCASTLE MICROWAVE STATION

WHITEVILLE, TENNESSEE

State of Tennessee
Department of Environment and Conservation
Division of Air Pollution Control
William R. Snodgrass Tennessee Tower
312 Rosa L. Parks Avenue, 15th Floor
Nashville, TN 37243
Telephone: (615) 532-0554



TN. DIV. CE AIR POLLUTION CONTROL

2015 MAY 20 PM 1: 06

NON-TITLE V PERMIT APPLICATION FACILITY IDENTIFICATION

Plea	se type or print and subn	nit in duplicate for each	ch emission source. A	Attach appropriate descri	ption.jorms.
		SITE	INFORMATION		
 Organization's legal nate Tennessee Valley Author Site name (if different forms) 	rity (TVA) - Newca	For APC Compa use APC Log/Pe	35-0107-01 970315		
3. Site address (St./Rd./H ⁻ 4745 Sommerville Road	wy.)			County name Hardeman	1 700/3
City or distance to neare	et tourn		Zip code	4. NAICS or SIC co	de
Whiteville, TN	st town		37075	4911	
5. Site location (in lat. /long,)	Latitude 35.202			Longitude -89.18	
	CON	TACT INFORMA	TION (RESPON	SIBLE PERSON)	
6. Responsible person/Au Billy R. Hall, Jr.	thorized contact			Phone number with area 423-751-6963	a code
Mailing address (St/Ro 1101 Market Street, MR				Fax number with area c	ode
City Chattanooga		State TN	Zip code 37402	Email address brhall1@tva.gov	
With the second	- Count on the S	CONTACT INFO	DRMATION (TE		
7. Principal technical con Taylor E. Korth	tact			Phone number with area 423-751-3162	a code
Mailing address (St/Ro 1101 Market Street, MR				Fax number with area c	ode
City Chattanooga		State TN	Zip code 37402	Email address tkorth@tva.gov	
		CONTACT IN	FORMATION (B		
8. Billing contact		CONTINUE	014.11101. (2	Phone number with area	a code
Jack G. Byars				423-751-2666	
Mailing address (St./Ro 1101 Market Street, BR				Fax number with area c 423-751-7011	ode
City Chattanooga		State TN	Zip code 37402	Email address jgbyars@tva.gov	
		EMISSION SO	OURCE INFORM	IATION	William Street
9. Emission source no. (no PEG-1	umber which uniquely id	lentifies this source)			
10. Brief description of em					
43.5 hp propane engine i Model Year.	for emergency gene	rator. Cummins	Generator Model	C20 N6. Cummins Eng	ine Model QSJ2.4. 2014
11. Normal operation:	Hours/Day 8.33	Days/W	eek	Weeks/Year	Days/Year 12
12. Percent annual throughput	Dec. – Feb. 25%	March – 25%	May	June – August	Sept – Nov. 25%
	12070			1	

13. Operating permit		TYPE OF P	ERMIT REQUESTED				
13. Operating permit	Date construction sta		Date completed	Las	t permit no.	Emission source	reference
()						number	
Construction permit	Last permit no			Em	ission source refere	nce number	
	East permit no					nee namber	
(X)				PE	J-1		
If you choose Construction permit				n transfer	Con Life day		
	New Construction		Starting date		Completion date		
	(X)	J	uly 2015		July 2015		
	Modification	I	Date modification started or	will start	Date completed of	r will complete	
	()						
	Location transfer		Transfer date		Address of last lo	cation	
	()		Transfer agree		1144.055 01145110		
19	· /						
14. Describe changes that have been	made to this equipm	ent or operati	ion since the last construct	ion or oper	ating permit appli	cation:	
N/A							
			IGNATURE				25
Based upon information and belief information contained in this applie							
information contained in this application 39-16-702(a)(4), this declar				to the best	of my knowledge	e. As specified in	ICA
15. Signature (application past be sig			Cijary .	Date	//		
13. Signiture (application)	delote it will be j	nocesseuj		05	/11/20	15	
as you					(
Signer's name (type of print)		Title			umber with area c	ode	
Billy R. Hall, Jr.		General M	lanager, Telecom	423-75	-6963		
If the system has several pieces of connect If none of the below codes fit, use 999 as a No Equipment	a code for other and sp	pecify in the co	omments.				
Activated Carbon Adsorption							041
Afterburner – Direct Flame		021					
Afterburner – Direct Flame with Heat Exc		U41	Liquid Filtration S	n – Wet ystem			042
Afterburner – Catalytic Afterburner – Catalytic with Heat Exchang		022	Liquid Filtration S Mist Eliminator –	n – Wet ystem High Veloci	y		042 049 014
Alkalized Alumina	er	022	Liquid Filtration S Mist Eliminator – I Mist Eliminator – I	n – Wet ystem High Veloci Low Velocit	yy		042 049 014 015
Catalytic Oxidation – Flue Gas Desulfuriza		022 019 020 040	Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change	n – Wet ystem High Veloci Low Velocit	yy		042 049 014 015
O I III E 00' '	ation		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov	n – Wet ystem High Veloci Low Velocit	y y 		042 049 014 015 046 054
	ation		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber –	n – Wet ystem High Veloci Low Velocit ery - High Effic	y		042 049 015 046 060 004
Cyclone – Medium Efficiency	ation		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber –	n – Wet ystem High Veloci Low Velocit ery High Effic Medium E	y y ency fficiency		042 049 014 046 046 060 004 005
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers	ation		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber –	n – WetystemHigh Velocit	y y ency fficiency ency		042 049 014 015 046 054 060 004 005 006
Cyclone – High Efficiency Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency	or Wetting Agents		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Sulfuric Acid Plant	n – Wet ystem High Veloci Low Velocit ery - High Effic - Medium E - Low Effici cous Control	y		042 049 015 046 060 004 005 006 006 052
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie	or Wetting Agents	022 019 020 040 039 007 008 009 062 010	Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Sulfuric Acid Plant Sulfuric Acid Plant	n – Wetystem	iency ency Only) Process		042 049 014 015 060 004 005 006 006 006 005 006 004 005 006
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency	or Wetting Agents		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber – Spray Tower (Gase Sulfuric Acid Plant Sulfuric Acid Plant	n – Wet	iency ency Only) Process		042 049 014 015 060 004 005 006 006 006 005 006 004 005 006
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature	or Wetting Agents		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber – Spray Tower (Gase Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosur	n – Wet	ency ency ency only) crocess contact Process ding Condensers, H	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature	or Wetting Agents		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber – Settling Chamber – Spray Tower (Gase Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery S Other Enclosus Venturi Scrubber (i	n – Wet	ency ency ency only) rocess ontact Process ding Condensers, H	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature Fabric Filter – Low Temperature Fabric Filter – Metal Screens (Cotton Gins	or Wetting Agents		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber – Settling Chamber – Spray Tower (Gase Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosus Venturi Scrubber (Wet Scrubber – Hi	n – Wet	ency ency ency only) contact Process ding Condensers, H	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column Packed	or Wetting Agents	022 019 020 040 039 007 008 009 062 010 011 012 016 017 018 059	Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Suffuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosur Venturi Scrubber (Wet Scrubber – Me Wet Scrubber – Me Wet Scrubber – Lo	n – Wet	iency y cency cency Only) corcess contact Process ding Condensers, H introl Only) y ency y	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficiency Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type	or Wetting Agents	022 019 020 040 039 007 008 009 062 010 011 012 016 017 018 059 023	Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Suffuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosur Venturi Scrubber (Wet Scrubber – Me Wet Scrubber – Me Wet Scrubber – Lo	n – Wet	iency y cency cency Only) corcess contact Process ding Condensers, H introl Only) y ency y	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature Fabric Filter – Low Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring	or Wetting Agents	022 019 020 040 039 007 008 009 062 010 011 012 016 017 018 059 023	Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Suffuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosur Venturi Scrubber (Wet Scrubber – Me Wet Scrubber – Me Wet Scrubber – Lo	n – Wet	iency y cency ency Only) corcess contact Process ding Condensers, H introl Only) y ency y	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficiency Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type	or Wetting Agents	022 019 020 040 039 007 008 009 010 011 012 016 017 018 059 023 050 051	Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Suffuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosur Venturi Scrubber (Wet Scrubber – Me Wet Scrubber – Me Wet Scrubber – Lo	n – Wet	iency y cency ency Only) corcess contact Process ding Condensers, H introl Only) y ency y	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column Packed Gas Adsorption Column - Tray Type Gas Scrubber (General: Not Classified)	or Wetting Agents		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Suffuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery S Other Enclosus Venturi Scrubber – Hi Wet Scrubber – Hi Wet Scrubber – Lo Wet Suppression by	n – Wet	iency y ency ency ency only) rocess ontact Process ding Condensers, H trol Only) y ency y ency	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type Gas Scrubber (General: Not Classified) Not application / Emissions are known to Emissions based on source testing	or Wetting Agents y ency Tal		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber – Spray Tower (Gase Sulfuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Sulfuric Serubber (Wet Scrubber – Hi Wet Scrubber – Hi Wet Scrubber – Lo Wet Suppression by n Estimation Method Code	n – Wet	ency fficiency ency Only) Process dontact Process ding Condensers, H	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type Gas Scrubber (General: Not Classified) Not application / Emissions are known to be Emissions based on source testing Emissions based on material balance using	or Wetting Agents y ency Tal		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber – Settling Chamber – Spray Tower (Gass Sulfuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosur Venturi Scrubber – Hi Wet Scrubber – Hi Wet Scrubber – Lo Wet Suppression by n Estimation Method Code	n – Wet	ency ency only) contact Process ding Condensers, H entrol Only)	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficie Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type Gas Scrubber (General: Not Classified) Not application / Emissions are known to be Emissions based on material balance using Emissions calculated using emission factor	or Wetting Agents y ency Tal pe zero engineering expertises from EPA publicati		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Settling Chamber – Settling Chamber – Settling Chamber – Spray Tower (Gass Sulfuric Acid Plant Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery S Other Enclosur Venturi Scrubber – Hi Wet Scrubber – Hi Wet Scrubber – Me Wet Scrubber – Lo Wet Suppression by n Estimation Method Code ge of process Compilation of Air Polluti	n – Wet	ency ency only) erocess ding Condensers, H entrol Only)	looding and	
Cyclone – Medium Efficiency Cyclone – Low Efficiency Dust Suppression by Chemical Stabilizers Electrostatic Precipitator – High Efficiency Electrostatic Precipitator – Medium Efficiency Electrostatic Precipitator – Low Efficiency Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Low Temperature Fabric Filter – Metal Screens (Cotton Gins Flaring Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type	Tal pe zero		Liquid Filtration S Mist Eliminator – I Mist Eliminator – I Process Change Process Enclosed Process Gas Recov Settling Chamber – Spray Tower (Gase Sulfuric Acid Plant Sulfuric Acid Plant Sulfur Plant Vapor Recovery Sy Other Enclosu Venturi Scrubber – Hi Wet Scrubber – Hi Wet Scrubber – Me Wet Scrubber – Lo Wet Suppression by In Estimation Method Code 12 Compilation of Air Polluti 42	n – Wet	ency fficiency ency Only) Process Iding Condensers, H entrol Only) y ency Ays	looding and	

State of Tennessee
Department of Environment and Conservation
Division of Air Pollution Control
William R. Snodgrass Tennessee Tower
312 Rosa L. Parks Avenue, 15th Floor
Nashville, TN 37243
Telephone: (615) 532-0554



NON-TITLE V PERMIT APPLICATION PROCESS OR FUEL BURNING SOURCE DESCRIPTION

Please type or print and sub	omit in duplicate and attach to th	ne Non-Title V Facility Id	entification	Form (APC 100)		
GE	ENERAL IDENTIFICATION	ON AND DESCRIPT	ION			
1. Organization name			AP	APC Company – Point no.		
Tennessee Valley Authority (TVA) - Oswa	ald Dome Microwave Stat		or			
2. Emission source no. (As on Non-Title V Facilit	ty Identification Form)		PC AP	C Log/Permit no.		
PEG-1			nly			
3. Description of process unit						
43.5 hp propane engine for emergency gen	erator. Cummins Engine	Model QSJ2.4. 20	14 Model	Year.		
The state of the s	PROCESS SOURCE DESC	CRIPTION AND DAT	ГА			
4. Type of source			(Cl	neck only one option below)		
Process Source: Apply for a separate Permit for each	source. (Check at right and cor	mplete lines 5, 6, and 11)		()		
Process Source with in process fuel: Products of com	houstion contact materials heater	d		()		
Apply for a separate permit for each source. (Check				()		
Non-Process fuel burning source: Products of combu	ustion do not contact materials h	neated.				
Complete this form for each boiler or fuel burner and	d complete a Non-Title V Emiss	sion Point Description Fo	rm	(🗙)		
(APC 101) for each stack, (Check at right and compl	ete lines 7 to 11)					
5. Type of operation:		Normal batch time	No	rmal batches/day		
Continuous ()	Batch ()					
6. Process material inputs and	Diagram reference		Input rate	es (pounds/hour)		
In-process solid fuels		Design		Actual		
A.						
В						
C.						
D,						
E:						
F,						
G.				-		
	Totals			2		

(Over)

^{*} A simple process flow diagram must be attached.

	L. D. J.	20	BOILER	R, BURNER, GE	NERATOR, O	R SIMILA	R FUEL B	URNII	NG PR	OCESS DESCR	IPTI	ON
7.	Boiler or bu	ırner		mplete lines 7 to 11								
Nu	Number Stack Type of firing***		*	Rated h	orsepower	Rated input capacity (10 ⁶ BTU/Hr.)		Other rating (specify capa	Other rating (specify capacity and units)			
		PE	G-1	Internal Comb	bustion	43.5	0.270					
Ser	ial no.		Date con		Date manufactur	ed	Date of la	st modif	ication (explain in commen	ts bel	ow)
			July/20	15	July/2015							
	*** Cyclone	e, spre	eader (with r other type	ack will have the sa or without reinject (describe below in	ion), pulverized (w comments)	et or dry bott						
				SED IN BOILE						L BURNING SO	DUR	CE
8.	Fuel data: (Primary fuel		**************************************	process source with	in process fuel or	a non-proces	A CONTRACTOR OF THE PARTY OF TH		ype(s) (s	manifu)		
	Primary rue	type	(specify)	ropane			Stand	by ruer i	ype(s) (s	pecity)		
	Fuels used			Annual usage	Hou	rly usage	9		%	BTU value		(For APC use only)
_					Design	Average		fur	Ash	of fuel		SCC code
	Natural gas:			10° Cu. Ft.	Cu. Ft.	Cu. Ft.	/ /		1 1	1,000		
	#2 Fuel oil:			10 ³ Gal	Gal.	Gal.			11			
	#5 Fuel oil:			10 ³ Gal	Gal.	Gal.			# / 			
	#6 Fuel oil:			10 ³ Gal.	Gal.	Gal.			11			
	Coal;			Tons	Lbs	Lbs.					П	
	Wood:			Tons	Lbs.	Lbs.	/ /		/ / / / /			
	Liquid propa	ne:		10 ³ Gal.	Gal	Gal.	11		11		Н	
				0.294	2.94	2.94	/ /	/ /	/ /	92,000		
	Other (specification):	y typ	e &									
9.	If Wood is u	ised a	ıs a fuel, sp	ecify types and es	timate percent by	weight of b	ark					
10.	If Wood is u	sed v	vith other	fuels, specify perc	ent by weight of v	vood charged	l to the bur	ner.				
11.	Comments											

State of Tennessee
Department of Environment and Conservation
Division of Air Pollution Control
William R. Snodgrass Tennessee Tower
312 Rosa L. Parks Avenue, 15th Floor
Nashville, TN 37243
Telephone: (615) 532-0554



NON-TITLE V PERMIT APPLICATION EMISSION POINT DESCRIPTION

Please type or print	and submit in d				urce, Attach to the No			nuncation Form (A	PC 100)	
		GENERA	L IDENTI	FICAT	ION AND DESCR	IPTIO	V		THE LABOR CO.	
1. Organization name							For	APC Company po	oint no.	
Tennessee Valley Author	ity (TVA) - 0	Oswald Dome	e Microwa	ve Stat	ion		APC use			
2. Emission source no. (As on Non-Title V Facility Identification Form) Flow diagram point number								APC Log/Permit	no.	
PEG-1 N/A										
3. Brief emission point descr	ription (Attach	a sketch if appro	priate):					Distance to neares	st property line (Ft.)	
43.5 hp propane engine fo	or emergency	generator. (Cummins I	Engine	Model QSJ2.4. 2	014 M	odel Yr			
		PETER P	STACK A	ND EM	IISSION DATA					
4. Stack or emission point data:	Height above	grade (Ft.)	Diameter ((Ft.)	Temperature (°F)	% of tir	ne over 125°	F Direction of e (Up, down or		
\rightarrow	4				1144					
Data at exit conditions:	Flow (actual	Ft.3/Min.)	Velocity (Ft,	Moisture (Grains/F	1,3)		Moisture (Per	cent)	
\rightarrow	110.7	/Sec.)								
Data at standard conditions:	Flow (Dry std. Ft. 3/Min.)		Velocity (Ft, Moisture (Grains/Ft, 5) /Sec.)		t. ³)		Moisture (Per	cent)		
\rightarrow										
5. Air contaminants			Actual emiss	sions						
	Emissions (Lbs./Hr.)									
	Average	Maximum		ntration	Avg. emissio (Tons/Yr.)		Emissions es method code		Control efficiency%	
Particulate matter	0.0147	0.0147	**		7.34E-04		5			
Sulfur dioxide (SO ₂)	0.00103	0.00103	***		5.14E-05		5			
Carbon monoxide (CO)	37.1	37.1	PPM		1.86		5			
Organic compounds			PPM							
Nitrogen oxides (NOx) + Hydrocarbons	0.959	0.959	PPM		0.0479		5			
Fluorides										
Greenhouse gases (CO ₂ equivalents)	37.6	37.6			1.88		5			
Hazardous air pollutant (specify))):					
Hazardous air pollutant (specify)										
Other (specify)										
Other (specify)										
Other (specify)										

6. Check types of r	nonitoring and recording ins	truments that are attach	ed:		
Opacity monitor	(), SO ₂ monitor (), NO _X monitor (), Other (specify in comments) ()	
7. Comments					
8. Control device or	Description of operating para	meters of device (flow ra	te, temperature, pressure drop, etc.):		
Method code	Description of operating part	aneters of device (now id	ite, temperature, pressure drop, etc.).		
description:					
	000				
	185				

Refer to the tables below for estimation method and control device codes.

Exit gas particulate matter concentration units: Process – Grains/Dry Standard Ft³ (70°F), Wood fired boilers - Grains/Dry Standard Ft³ (70°F), all other boilers – Lbs. /Million BTU heat input.

Exit gas sulfur dioxide concentrations units: Process - PPM by volume, dry bases, and boilers - Lbs. /Million BTU heat input

<u>Table of Pollution Reduction Device or Method Codes</u> (Alphabetical listing)

Note: For cyclones, settling chambers, wet scrubbers, and electrostatic precipitators; the efficiency ranges correspond to the following percentages:

High: 95-99+%. Medium: 80-95% And Low: Less than 80%.

If the system has several pieces of connected control equipment, indicate the sequence. For example: 008'010.97% If none of the below codes fit, use 999 as a code for other and specify in the comments.

No Equipment	000	Limestone Injection – Dry	041
Activated Carbon Adsorption	048	Limestone Injection – Wet	042
Afterburner - Direct Flame	021	Liquid Filtration System	049
Afterburner - Direct Flame with Heat Exchanger	022	Mist Eliminator - High Velocity	014
Afterburner – Catalytic	019	Mist Eliminator - Low Velocity	015
Afterburner - Catalytic with Heat Exchanger		Process Change	
Alkalized Alumina	040	Process Enclosed	054
Catalytic Oxidation - Flue Gas Desulfurization	039	Process Gas Recovery	060
Cyclone – High Efficiency	007	Settling Chamber – High Efficiency	004
Cyclone - Medium Efficiency	800	Settling Chamber – Medium Efficiency	005
Cyclone – Low Efficiency	009	Settling Chamber – Low Efficiency	006
Dust Suppression by Chemical Stabilizers or Wetting Agents	062	Spray Tower (Gaseous Control Only)	052
Electrostatic Precipitator – High Efficiency	010	Sulfuric Acid Plant - Contact Process	043
Electrostatic Precipitator – Medium Efficiency	011	Sulfuric Acid Plant - Double Contact Process	044
Electrostatic Precipitator - Low Efficiency	012	Sulfur Plant	045
Fabric Filter - High Temperature	016	Vapor Recovery System (Including Condensers, Hooding and	
Fabric Filter – Medium Temperature	017	Other Enclosures)	047
Fabric Filter – Low Temperature	018	Venturi Scrubber (Gaseous Control Only)	053
Fabric Filter - Metal Screens (Cotton Gins)		Wet Scrubber - High Efficiency	
Flaring		Wet Scrubber - Medium Efficiency	002
Gas Adsorption Column Packed	050	Wet Scrubber - Low Efficiency	003
Gas Adsorption Column - Tray Type		Wet Suppression by Water Sprays	
Gas Scrubber (General: Not Classified)	013	, , , , , , , , , , , , , , , , , ,	

Table of Emission Estimation Method Codes

Not application / Emissions are known to be zero	.0
Emissions based on source testing	. 1
Emissions based on material balance using engineering expertise and knowledge of process	.2
Emissions calculated using emission factors from EPA publications No. AP-42 Compilation of Air Pollution Emissions Factors	
Tudgment	4
Emissions calculated using a special emission factor different from that in AP-42	. 5
Other (Specify in comments)	

Table 1. Small Emergency Propane Generator Engine at Oswald Dome Microwave Station in Reliance, Tennessee

Emission Source				Oswald Dome Mid	crowave Station Engine
Engine Model Year					2015
Propane Engine Horsepower, hp*					43.5
Propane Fuel Heat Content, Btu/gal				9	2,000
Propane Fuel Use, gal/hr*					2.94
Propane Engine Heat Input Rating, MMBtu/hr					0.270
Potential Annual Hours of Operation, hr**					100
	US EPA				
	Emission Standards	Emission Factor***	Emission Factor****	En	nissions
	g/hphr	lb/1000 gal	lb/MMBtu	lb/hr	ton/yr**
Particulate Matter (PM ₁₀)		5		0.0147	7.34E-04
Nitrogen Oxides (NOx) + Hydrocarbons (HC)	10			0.959	0.0479
Carbon Monoxide (CO)	387			37.1	1.86
Sulfur Dioxide (SO ₂)		0.35		0.00103	5.14E-05
Carbon Dioxide Equivalent (CO ₂ e)			139.2	37.6	1.88

^{*} Based on information from manufacturer, Cummins Power Generation.

^{**} Potential annual emissions based on 100 hours per year of operation. This is not a permit restriction.

^{***} San Diego Air Pollution Control District, Air Toxics Section (6/99), Uncontrolled Propane Fired Internal Combustion Engine.

^{****} CO_2 factor is 62.87 kg CO_2 /MMBtu, CH_4 factor is 0.003 kg CH_4 /MMBtu, N_2O factor is 0.0006 kg N_2O /MMBtu.

CO₂ equivalent factor for CO₂ is 1, CO₂ equivalent factor for CH₄ is 25, CO₂ equivalent factor for N₂O is 298.



ZP4508

\$102 20181:10

1030

t ac . ac	